



SC-615BS Paging Horn Speaker EN54



- 15W Input (mobile mount, 10W).
- Certified according EN54-24 for voice alarm systems.
- Stainless steel brackets and hardware.
- Shock resistant aluminium oval horn.
- Unobtrusive off-white colour.
- Compliance with IP-65.

Specification

Rated Input	15W (100V Line and 70V Line)
Rated Impedance	100V : 670Ω (15W), 1kΩ(10W), 2kΩ(5W),3.3kΩ(3W) 70V : 330Ω(15W), 670Ω(7.5W), 1kΩ(5W), 2kΩ(2.5W), 3.3kΩ(1.5W)
Sound Pressure Level	109dB, 1W / 1m at 500 to 2,500 Hz peak level
Max Sound Pressure Level	110 dB
Frequency Response	315 ~ 12,500Hz
IP Grade	IP65
Polarity	Hot; Black wire, com; White wire
Operating Temperature	-20 ~ +55°C (must be free from dew condensation)
Finish	Horn flare: Aluminum, off-white, powder coating / Reflector horn and rear cover: ABS resin, off-white / Bracket, Screws and bolts: Stainless steel / Speaker cable: Polyvinyl chloride insulated cabtyre cable (6 mm in diameter, 600 mm in length)
Dimensions	172 (W) x 195 (H) x 229 (D) mm
Weight	1.5 kg Material Aluminium